Serial No.: 10/774,985 Filed: February 9, 2004

Page : 2 of 11

## Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## Listing of Claims:

1. (Currently Amended) An ultrasonic medical device comprising:

an ultrasonic probe comprising a proximal end, a distal end and a longitudinal axis therebetween;

- a transducer creating a torsional vibration of the ultrasonic probe;
- a coupling engaging the proximal end of the ultrasonic probe to a distal end of the transducer; and

an ultrasonic energy source engaged to the transducer that produces an ultrasonic energy, wherein the ultrasonic probe is configured to produce cavitation along the longitudinal axis in a medium surrounding the probe during use.

- 2. (Original) The ultrasonic medical device of claim 1 wherein the torsional vibration of the ultrasonic probe causes a rotation and counterrotation along the longitudinal axis of the ultrasonic probe.
- 3. (Original) The ultrasonic medical device of claim 1 wherein the torsional vibration of the ultrasonic probe is propagated in a forward direction and a reverse direction about a plurality of torsional nodes along a portion of the longitudinal axis of the ultrasonic probe.
- 4. (Original) The ultrasonic medical device of claim 1 wherein a portion of the longitudinal axis of the ultrasonic probe comprises a radially asymmetric cross section.

Serial No.: 10/774,985 Filed: February 9, 2004

Page : 3 of 11

5. (Currently Amended) The ultrasonic medical device of claim 4 wherein the cavitation occurs around the portion of the longitudinal axis of the ultrasonic probe comprising the radially

asymmetric cross section to ablate a biological material.

6. (Original) The ultrasonic medical device of claim 1 wherein the torsional vibration of the

ultrasonic probe produces a plurality of torsional nodes and a plurality of torsional anti-nodes

along a portion of the longitudinal axis of the ultrasonic probe.

7. (Original) The ultrasonic medical device of claim 1 wherein a length of the longitudinal axis

of the ultrasonic probe comprises an approximately rectangular shaped cross section.

8. (Original) The ultrasonic medical device of claim 1 wherein a length of the longitudinal axis

of the ultrasonic probe comprises a spline shape.

9. (Original) The ultrasonic medical device of claim 1 wherein a plurality of projections extend

from an outer surface along a length of the ultrasonic probe.

10. (Original) The ultrasonic medical device of claim 1 wherein a length of the longitudinal axis

of the ultrasonic probe has a cross sectional shape selected from the group consisting of

elliptical, star shaped, rectangular, oval, triangular, trapezoidal, circular with a flat spot and

square.

11. (Original) The ultrasonic medical device of claim 1 wherein the torsional vibration generates

acoustic energy in a medium surrounding the ultrasonic probe.

12. (Original) The ultrasonic medical device of claim 1 wherein the ultrasonic energy source

delivers ultrasonic energy in a frequency range from about 10 kHz to about 100kHz.

13. (Cancelled).

Serial No.: 10/774,985 Filed: February 9, 2004

Page : 4 of 11

14. (Original) The ultrasonic medical device of claim 1 wherein the ultrasonic probe supports the torsional vibration when flexed.

15. (Original) The ultrasonic medical device of claim 1 wherein the ultrasonic probe has a flexibility allowing the ultrasonic probe to be deflected and articulated.

- 16. (Original) The ultrasonic medical device of claim 1 wherein the ultrasonic probe comprises a substantially uniform cross section from the proximal end of the ultrasonic probe to the distal end of the ultrasonic probe.
- 17. (Original) The ultrasonic medical device of claim 1 wherein the ultrasonic probe comprises a varying cross section from the proximal end of the ultrasonic probe to the distal end of the ultrasonic probe.
- 18. (Original) The ultrasonic medical device of claim 1 wherein the ultrasonic probe is disposable.
- 19. (Currently Amended) A medical device comprising:

an elongated probe comprising a proximal end, a distal end, and a longitudinal axis between the proximal end and the distal end wherein a portion of the longitudinal axis comprises a radially asymmetric cross section;

a transducer that converts electrical energy into mechanical energy, creating a torsional vibration along the longitudinal axis of the elongated probe;

a coupling engaging the proximal end of the elongated probe to a distal end of the transducer; and

an ultrasonic energy source engaged to the transducer that provides the electrical energy to the transducer,

wherein the torsional vibration along the elongated probe produces a plurality of torsional nodes and a plurality of torsional anti-nodes along a portion of the longitudinal axis of the elongated probe, and

Serial No.: 10/774,985 Filed: February 9, 2004

Page : 5 of 11

wherein the ultrasonic probe is configured to produce cavitation along the longitudinal axis in a medium surrounding the probe during use.

20. (Original) The medical device of claim 19 wherein the torsional vibration of the elongated probe produces a rotation and a counterrotation along the longitudinal axis of the elongated probe.

- 21. (Original) The medical device of claim 19 wherein the torsional vibration of the elongated probe is propagated in a forward direction and a reverse direction about the plurality of torsional nodes of the elongated probe.
- 22. (Original) The medical device of claim 19 wherein the torsional vibration generates acoustic energy in a medium surrounding the elongated probe.
- 23. (Currently Amended) The medical device of claim 19 wherein the cavitation occurs over an active area of the elongated probe along the portion of the longitudinal axis comprising the radially asymmetric cross section.
- 24. (Currently Amended) The medical device of claim [[29]] 19 wherein a length of the longitudinal axis of the elongated probe comprises a spline shape.
- 25. (Original) The medical device of claim 19 wherein a length of the longitudinal axis of the elongated probe has a cross sectional shape selected from the group consisting of elliptical, star shaped, rectangular, oval, triangular, trapezoidal, circular with a flat spot and square.
- 26. (Original) The medical device of claim 19 wherein a plurality of projections extend from an outer surface along a length of the elongated probe.
- 27. (Original) The medical device of claim 19 wherein the ultrasonic energy source delivers ultrasonic energy in a frequency range from about 10 kHz to about 100 kHz.

Serial No.: 10/774,985 Filed: February 9, 2004

Page : 6 of 11

28. (Cancelled).

29. (Original) The medical device of claim 19 wherein the elongated probe supports the torsional vibration when flexed.

- 30. (Original) The medical device of claim 19 wherein the elongated probe has a flexibility allowing the elongated probe to be deflected and articulated.
- 31. (Original) The medical device of claim 19 wherein the elongated probe comprises a substantially uniform cross section from the proximal end of the elongated probe to the distal end of the elongated probe.
- 32. (Original) The medical device of claim 19 wherein the elongated probe comprises a varying cross section from the proximal end of the elongated probe to the distal end of the elongated probe.
- 33 63. (Canceled).
- 64. (Currently Amended) An ultrasonic probe comprising:
  - a proximal end;
  - a distal end that terminates in a probe tip; and
- a longitudinal axis between the proximal end and the distal end, a portion of the longitudinal axis of the ultrasonic probe comprising a radially asymmetric cross section to support a torsional vibration,

wherein the ultrasonic probe is configured to produce cavitation along the longitudinal axis in a medium surrounding the probe during use.

Serial No.: 10/774,985 Filed: February 9, 2004

Page : 7 of 11

65. (Original) The ultrasonic probe of claim 64 wherein the ultrasonic probe comprises a varying cross section from the proximal end of the ultrasonic probe to the distal end of the ultrasonic

probe.

66. (Original) The ultrasonic probe of claim 64 wherein a cross section of the proximal end of

the ultrasonic probe is approximately circular.

67. (Original) The ultrasonic probe of claim 64 wherein the radially asymmetric cross section

comprises a spline shape.

68. (Original) The ultrasonic probe of claim 64 wherein the radially asymmetric cross section has

a cross sectional shape selected from the group consisting of elliptical, star shaped, rectangular,

oval, triangular, trapezoidal, circular with a flat spot and square.

69. (Previously Presented) The ultrasonic probe of claim 64 wherein the ultrasonic probe

comprises a varying diameter from the proximal end of the ultrasonic probe to the distal end of

the ultrasonic probe.

70. (Original) The ultrasonic probe of claim 64 wherein the ultrasonic probe has a flexibility

allowing the ultrasonic probe to be deflected and articulated.

71. (Canceled).

72. (New) The ultrasonic medical device of claim 1 wherein, during use, the ultrasonic energy

source provides an electrical power to the transducer at a resonant frequency of the transducer by

finding the resonant frequency of the transducer.

73. (New) The medical device of claim 19 wherein, during use, the ultrasonic energy source

provides an electrical power to the transducer at a resonant frequency of the transducer by

finding the resonant frequency of the transducer.

Attorney's Docket No.: 18554-035001 Applicant: Robert A. Rabiner et al.

Serial No.: 10/774,985 Filed : February 9, 2004 Page : 8 of 11

74. (New) The ultrasonic medical device of claim 1, wherein a length of the probe is substantially equal to an integer multiple of a one-half wavelength of a torsional resonance of the transducer.

75. (New) The medical device of claim 19, wherein a length of the probe is substantially equal to an integer multiple of a one-half wavelength of a torsional resonance of the transducer.